



- We declare that the material of product compliance with RoHS requirements.
- S- Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable.

### ORDERING INFORMATION

Device	Marking	Shipping
MBT2907LT1G,S-LMBT2907LT1G	M2B	3000/Tape & Reel
MBT2907LT3G,S-LMBT2907LT3G	M2B	10000/Tape & Reel
MBT2907ALT1G,S-LMBT2907ALT1G	2F	3000/Tape & Reel
MBT2907ALT3G,S-LMBT2907ALT3G	2F	10000/Tape & Reel



### MAXIMUM RATINGS

Rating	Symbol	Value		Unit
		2907	2907A	
Collector–Emitter Voltage	$V_{CE0}$	-40	-60	Vdc
Collector–Base Voltage	$V_{CBO}$		-60	Vdc
Emitter–Base Voltage	$V_{EBO}$		-5.0	Vdc
Collector Current — Continuous	$I_C$		-600	mAdc

### THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation FR-5 Board, (1) $T_A = 25^\circ\text{C}$	$P_D$	225	mW
Derate above $25^\circ\text{C}$		1.8	mW/ $^\circ\text{C}$
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	556	$^\circ\text{C}/\text{W}$
Total Device Dissipation Alumina Substrate, (2) $T_A = 25^\circ\text{C}$	$P_D$	300	mW
Derate above $25^\circ\text{C}$		2.4	mW/ $^\circ\text{C}$
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	417	$^\circ\text{C}/\text{W}$
Junction and Storage Temperature	$T_J, T_{stg}$	-55 to +150	$^\circ\text{C}$

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. FR-5 =  $1.0 \times 0.75 \times 0.062$  in.
2. Alumina =  $0.4 \times 0.3 \times 0.024$  in. 99.5% alumina.

**ELECTRICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$  unless otherwise noted.)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

**OFF CHARACTERISTICS**

Collector–Emitter Breakdown Voltage(3) ( $I_C = -10\text{ mAdc}$ , $I_E = 0$ )	MBT2907 MBT2907A	$V_{(BR)CEO}$	-40 -60	— —	Vdc
Collector–Emitter Breakdown Voltage( $I_C = -10\ \mu\text{Adc}$ , $I_E = 0$ )		$V_{(BR)CBO}$	-60	—	Vdc
Emitter–Base Breakdown Voltage( $I_E = -10\ \mu\text{Adc}$ , $I_C = 0$ )		$V_{(BR)EBO}$	-5.0	—	Vdc
Collector Cutoff Current( $V_{CB} = -30\text{Vdc}$ , $I_{BE(OFF)} = -0.5\text{Vdc}$ )		$I_{CEX}$	—	-50	nAdc
Collector Cutoff Current ( $V_{CB} = -50\text{Vdc}$ , $I_E = 0$ )	MBT2907 MBT2907A	$I_{CBO}$	— —	-0.020 -0.010	$\mu\text{Adc}$
( $V_{CB} = -50\text{Vdc}$ , $I_E = 0$ , $T_A = 125^\circ\text{C}$ )	MBT2907 MBT2907A		— —	-20 -10	
Base Current( $V_{CE} = -30\text{Vdc}$ , $V_{EB(OFF)} = -0.5\text{Vdc}$ )		$I_B$	—	-50	nAdc

**ON CHARACTERISTICS**

DC Current Gain ( $I_C = -0.1\text{mAdc}$ , $V_{CE} = -10\text{ Vdc}$ )	MBT2907 MBT2907A	$h_{FE}$	35 75	— —	
( $I_C = -1.0\text{mAdc}$ , $V_{CE} = -10\text{ Vdc}$ )	MBT2907 MBT2907A		50 100	— —	
( $I_C = -10\text{ mAdc}$ , $V_{CE} = -10\text{Vdc}$ )	MBT2907 MBT2907A		75 100	— —	
( $I_C = -150\text{mAdc}$ , $V_{CE} = -10\text{ Vdc}$ )(3)	MBT2907 MBT2907A		— 100	— 300	
( $I_C = -500\text{mAdc}$ , $V_{CE} = -10\text{ Vdc}$ )(3)	MBT2907 MBT2907A		30 50	— —	
Collector–Emitter Saturation Voltage(3) ( $I_C = -150\text{mAdc}$ , $I_B = -15\text{ mAdc}$ ) ( $I_C = -500\text{ mAdc}$ , $I_B = -50\text{ mAdc}$ )		$V_{CE(sat)}$	— —	-0.4 -1.6	Vdc
Base–Emitter Saturation Voltage(3) ( $I_C = -150\text{mAdc}$ , $I_B = -15\text{ mAdc}$ ) ( $I_C = -500\text{mAdc}$ , $I_B = -50\text{ mAdc}$ )		$V_{BE(sat)}$	— —	-1.3 -2.6	Vdc

3. Pulse Test: Pulse Width  $\leq 300\ \mu\text{s}$ , Duty Cycle  $\leq 2.0\%$ .

### ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted) (Continued)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

#### SMALL-SIGNAL CHARACTERISTICS

Current-Gain — Bandwidth Product(3),(4) ( $I_C = -50\text{mA}$ , $V_{CE} = -20\text{V}$ , $f = 100\text{MHz}$ )	$f_T$	200	—	MHz
Output Capacitance ( $V_{CB} = -10\text{V}$ , $I_E = 0$ , $f = 1.0\text{MHz}$ )	$C_{obo}$	—	8.0	pF
Input Capacitance ( $V_{EB} = -2.0\text{V}$ , $I_C = 0$ , $f = 1.0\text{MHz}$ )	$C_{ibo}$	—	30	pF

#### SWITCHING CHARACTERISTICS

Turn-On Time	( $V_{CC} = -30\text{V}$ , $I_C = -150\text{mA}$ , $I_{B1} = -15\text{mA}$ )	$t_{on}$	—	45	ns
Delay Time		$t_d$	—	10	ns
Rise Time		$t_r$	—	40	ns
Fall Time	( $V_{CC} = -6.0\text{V}$ , $I_C = -150\text{mA}$ , $I_{B1} = I_{B2} = 15\text{mA}$ )	$t_f$	—	60	ns
Storage Time		$t_s$	—	225	ns
Turn-Off Time		$t_{off}$	—	280	ns

4.  $f_T$  is defined as the frequency at which  $|h_{fe}|$  extrapolates to unity.

### TYPICAL CHARACTERISTICS




Figure 1. Delay and Rise Time Test Circuit






Figure 2. Storage and Fall Time Test Circuit


**TYPICAL CHARACTERISTICS**




**Figure 3. DC Current Gain**



**Figure 4. Collector Saturation Region**



**Figure 5. Turn-On Time**




**Figure 6. Turn-Off Time**


**TYPICAL SMALL-SIGNAL CHARACTERISTICS**

**NOISE FIGURE**


$V_{CE} = 10 \text{ Vdc}, T_A = 25^\circ\text{C}$




**Figure 7. Frequency Effects**




**Figure 8. Source Resistance Effects**




**Figure 9. Capacitances**



**Figure 10. Current-Gain - Bandwidth Product**




**Figure 11. Collector Emitter Saturation Voltage vs. Collector Current**




**Figure 12. Base Emitter Saturation Voltage vs. Collector Current**

**TYPICAL SMALL-SIGNAL Characteristics**  
**NOISE FIGURE**


$V_{CE} = 10 \text{ Vdc}$ ,  $T_A = 25^\circ\text{C}$



**Figure 13. Base Emitter Voltage vs. Collector Current**




**Figure 14. Temperature Coefficients**



**Figure 15. Safe Operating Area**

**SOT-23**



**NOTES:**

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.1102	0.1197	2.80	3.04
B	0.0472	0.0551	1.20	1.40
C	0.0350	0.0440	0.89	1.11
D	0.0150	0.0200	0.37	0.50
G	0.0701	0.0807	1.78	2.04
H	0.0005	0.0040	0.013	0.100
J	0.0034	0.0070	0.085	0.177
K	0.0140	0.0285	0.35	0.69
L	0.0350	0.0401	0.89	1.02
S	0.0830	0.1039	2.10	2.64
V	0.0177	0.0236	0.45	0.60

- PIN 1. BASE  
 2. EMITTER  
 3. COLLECTOR

